TECHNICAL DATA SHEET







REACTION TIME

works during operation



APPLICATION FIELD

tank application for diesel engines with DPF



CONSUMPTION

50 ml per 1 L



APPLICATION INTERVAL

on demand

APPLICATION

Add regularly every 2.000 km right before filling up the tank. Sufficient for 40-60 L of diesel fuel. Product works during operation.

DESCRIPTION

DPF Purifier is a high-performance additive for use in all diesel aggregates to reduce soot and exhaust gas emissions and to increase engine performance. Compatible with all diesel engines without on-board additive dosing system and suitable for all kind of diesel fuels.

ADVANTAGES

Only a clean fuel system guarantees optimal operation of all system components, an efficient engine performance and minimum exhaust emissions. Protects the diesel particulate filter and the environment. Reduces soot formation and supports the regeneration of the diesel particulate filter. Increases cold start properties. Regular use helps to keep the filter clean and avoids expensive repair works.

CONTENT	PU	ART. NO.
300 ml	24 x 300 ml	Art. 09028
other sizes available on request		

PROPERTIES

Physical state	liquid
Color	clear, dark brown
Density	0,79-0,81 g/cm³
Flash point	>61 °C
Viscosity	<7 mm²/s

COMPATIBILITY

The product is suitable for use in all diesel engines with downstream diesel particulate filter and can be mixed with all diesel fuels.

SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

DISPOSAL

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.

MADE IN GERMANY