TECHNICAL DATA SHEET







REACTION TIME

works during application



APPLICATION FIELD

for use in all automatic transmission with torque converter



CONSUMPTION

60 ml for 1 L



APPLICATION INTERVAL

on demand

APPLICATION

Add to the warm engine oil after every oil change or when required. Works during operation.

Sufficient to treat 5 L of engine oil. For larger volumes add 60 ml product per liter engine oil. Compatible with all mineral and synthetic engine oils.

Attention: Check engine oil level before application!

We recommend cleaning of the oil system with Engine Cleaners before application.

DESCRIPTION

Hydraulic Lifter Care & Protect contains a high performance package of effective additives for improved high pressure properties as well as wear and tear protection of all types of engine oils.

ADVANTAGES

Only a well-functioning engine can run on full power! Disturbing rattle sounds will be eliminated. Reduction of wear and tear due to optimized lubrication.

CONTENT	PU	ART. NO.
300 ml	24 x 300 ml	Art. 09073
other sizes available on request		

PROPERTIES

Physical state	viscous liquid	
Color	yellow - amber	
Density	0,9 g/cm³	
Flash point	>100 °C	
Viscosity	>20 mm²/s (@ 40 °C)	

COMPATIBILITY

Compatible with all mineral and synthetic engine oils.

SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

DISPOSAL

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.

MADE IN GERMANY