TECHNICAL DATA SHEET







REACTION TIME works during operation



APPLICATION FIELD for use in all diesel engines



CONSUMPTION 50 ml for 10 L



APPLICATION INTERVAL with every tank filling

APPLICATION

Recommended to add to the diesel tank before every refueling. Sufficient for 60-80 liters of diesel. For larger capacities add 50 ml per 10 liters of diesel fuel. Product works during operation.

DESCRIPTION

Diesel System Cleaner PLUS is a high performance product for use in all diesel engines, particularly developed for high pressure direct injection diesel engines with common rail technology or pump injectors. Especially recommended for extended service intervals. Reliably removes operationally caused depositions in the whole diesel system from the tank to the combustion chamber. Absorbs and efficiently removes moisture from the diesel system and ensures effective protection of the high-pressure pump. Provides an optimal fuel spray pattern and protects all diesel carrying parts against corrosion. Ideally suited for vehicles with diesel particle filters.

ADVANTAGES

Optimize fuel atomization, improved engine performance, reduced diesel consumption and less exhaust emissions.

CONTENT	PU	ART. NO.
300 ml	24 x 300 ml	Art. 09397
other sizes available on request		

PROPERTIES

Physical state	liquid
Color	light yellow
Density	0,82 g/cm³ DIN 12185
Flash point	46 °C ISO 3679
Viscosity	1,3 mm²/s DIN EN ISO 3104 (at 40°)

COMPATIBILITY

The product is suitable for use in all diesel engines and can be mixed with all diesel fuels.

SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

DISPOSAL

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. Dispose of this product and container according to national/ regional regulations.



PLUS





MADE IN GERMANY

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.

Automobiltechnologie mbH & Co. KG Alt Saale 2

D - 07407 Uhlstädt-Kirchhasel

Phone: +49 (0) 3672 48380-66 Fax: +49 (0) 3672 48380-22 eMail: info@gat-international.de web: www.gat-international.de Geschäftsführerin I Managing Director Dr. Gaby Urban - Moscow State Pe Amtsgericht Gera HRB 503668 Ust.ID: DE297820562

revision status: 26.01.2023

GAT Gesellschaft für Kraftstoff - und