







## FUEL SYSTEM

# OCTANE BOOSTER MAX

OKTANBOOSTER MAX

-  **REACTION TIME**  
works during operation
-  **APPLICATION FIELD**  
for use in all gasoline engines
-  **CONSUMPTION**  
100 ml per 15 L
-  **APPLICATION INTERVAL**  
with every tank filling

### APPLICATION

Vor jeder Betankung zugeben. Ausreichend für 45 Liter Kraftstoff. Bei größerer Füllmenge 100 ml pro 15 Liter Kraftstoff zugeben.

### DESCRIPTION

**Octane Booster MAX** to increase the octane number of low octane fuels or for use in engines with higher octane requirements.

### ADVANTAGES

Protects valve seats while running on unleaded fuel. Improves start and full-load performance. Provides smoother idling. Prevents deposits on valves and in the combustion chamber. Increases the octane number by 3 up to 8 points. Improved engine performance and operational reliability. Protects valve seat from excessive wear. Ensures stable combustion process and an improved CO-value.

CONTENT	PU	ART. NO.
300 ml	24 x 300 ml	Art. 09411
other sizes available on request		

### PROPERTIES

Physical state	liquid
Color	yellow/orange - brown
Density	0,89 g/cm <sup>3</sup>
Flash point	24 °C

### COMPATIBILITY

Recommended for all gasoline engines.

### SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

### DISPOSAL

Dispose of this product and container according to national/ regional regulations.