TECHNICAL DATA SHEET





APPLICATION

1) Add the product to the coolant. 2) Run the engine at idle (depending on the size of the system) approx. 15-45 minutes to reach the operation temperatur. 3) After draining rinse thoroughly with water. 4) Now carry out the exchange of the coolant according to the manufacturer's instructions. Suitable for all closed water cooling systems and also for heat exchangers.

Attention: Open radiator filling port slowly and successively – risk of burning!

Sufficient for up to 10 liters of cooling liquid. For larger quantities, use the mixing ratio 1:20. Application interval: before every change of coolant.

DESCRIPTION


Radiator Cleaner removes all operational deposits in the entire cooling system as well as lime and fur deposits, dissolves dangerous radiator sludge and cleans water coolers, boilers and heat exchangers. Valves, thermostats and water pumps return to their optimal performance.

ADVANTAGES

The major part of chemical energy that is bound in the fuel is converted into heat during the combustion process which must be dissipated. Therefore a fully functional cooling system is of major importance for the operational liability of engines! Improved heating and cooling performance. Increases the operational liability of the cooling system and extends the life span of all aggregates.

CONTENT	PU	ART. NO.
300 ml	12 x 300 ml	Art. 09413
All an aire a sustituit a second at		

other sizes available on request



PROPERTIES

Physical state	liquid
Color	colourless
Density	1,07 g/cm³

COMPATIBILITY

Compatible with all water-cooled, closed cooling systems (commercial vehicles, cars, other industrial heat exchangers).

SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

DISPOSAL

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.

GAT Gesellschaft für Kraftstoff - und Automobiltechnologie mbH & Co. KG Alt Saale 2 D - 07407 Uhlstädt-Kirchhasel Phone:+49 (0) 3672 48380-66 Fax: +49 (0) 3672 48380-22 eMail: info@gat-international.de web: www.gat-international.de Geschäftsführerin I Managing Director Dr. Gaby Urban – Moscow State Pedagogical University Amtsgericht Gera HRB 503668 Ust.ID: DE297820562 MADE IN GERMANY

revision status: 26.01.2023