TECHNICAL DATA SHEET







REACTION TIME works during operation



APPLICATION FIELD for use in all gasoline engines



CONSUMPTION 50 ml per 10 L



APPLICATION INTERVAL with every tank filling

APPLICATION

Recommended to add to the petrol tank before every refueling. Sufficient for 40-60 liters of petrol. For larger capacities add 50 ml per 10 liter fuel. Product works during the operation.

DESCRIPTION

Fuel System Cleaner PLUS is suitable for use in all petrol engines, generators and high-performance engines (e.g. boat, bike etc.). Solves operationally caused contamination in the entire fuel system from the tank to the combustion chamber. Dissolves resinifications and gums in the carburetor and injection system. Removes coking and unburned carbon residues in the upper cylinder area. Reliably binds moisture from the fuel and prevents condensation to prevent failure.

ADVANTAGES

Clean and powerful combustion process and highly efficient engine running. The product has a positive impact on fuel consumption, improved engine performance and reduced exhaust gas emissions. Protects against corrosion, which increases the life of injectors and fuel pumps. Has a positive effect for the lifetime of the catalyst.

CONTENT	PU	ART. NO.
300 ml	24 x 300 ml	Art. 09014
other sizes available on request		

PROPERTIES

Physical state	liquid
Color	red
Density	0,82 g/cm³ DIN 12185
Flash point	-9 °C ISO 3679
Viscosity	0,73 mm²/s (at 40 °C) DIN EN ISO 3104

COMPATIBILITY

Recommended for all gasoline engines.

SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

DISPOSAL

Dispose of this product and container according to national/ regional regulations.





MADE IN GERMANY